



Corrugated Panel

SECTION PROPERTIES								
			NEGATIVE BENDING			POSITIVE BENDING		
PANEL	Fy	WEIGHT	Ixe	Sxe	Maxo	Ixe	Sxe	Maxo
GAUGE	(KSI)	(PSF)	(IN.4/FT.)	(IN.3/FT.)	(KIP-IN.)	(IN.4/FT.)	(IN.3/FT.)	(KIP-IN.)
29	60*	0.60	0.0065	0.0147	0.5279	0.0069	0.0170	0.5648
26	60*	0.79	0.0088	0.0200	0.7200	0.0088	0.0225	0.7393

* Fy is 80-ksi reduced to 60-ksi in accordance with the 2001 edition of the North American Specification For Design Of Cold-Formed Steel Structural Members - A2.3.2.

NOTES:

1. All calculations for the properties of Corrugated panels are calculated in accordance with the 2001 edition of the North American Specification For Design Of Cold-Formed Steel Structural Members.
2. Ixe is for deflection determination.
3. Sxe is for bending.
4. Maxo is allowable bending moment.
5. All values are for one foot of panel width.

The Engineering data contained herein is for the expressed use of customers and design professionals. Along with this data, it is recommended that the design professional have a copy of the most current version of the *North American Specification for the Design of Cold-Formed Steel Structural Members* published by the American Iron and Steel Institute to facilitate design. This Specification contains the design criteria for cold-formed steel components. Along with the Specification, the designer should reference the most current building code applicable to the project jobsite in order to determine environmental loads. If further information or guidance regarding cold-formed design practices is desired, please contact the manufacturer.



ALLOWABLE UNIFORM LOADS IN POUNDS PER SQUARE FOOT

Corrugated Panel

29 Gauge (Fy = 60 KSI)								
SPAN TYPE	LOAD TYPE	SPAN IN FEET						
		2.0	2.5	3.0	3.5	4.0	4.5	5.0
SINGLE	NEGATIVE WIND LOAD	88.0	56.3	39.1	28.7	22.0	17.4	14.1
	LIVE LOAD/DEFLECTION	75.4	38.6	22.3	14.1	9.4	6.6	4.8
2-SPAN	NEGATIVE WIND LOAD	94.1	60.2	41.8	30.7	23.5	18.6	15.1
	LIVE LOAD/DEFLECTION	81.4	56.3	39.1	28.7	22.0	15.9	11.6
3-SPAN	NEGATIVE WIND LOAD	117.7	75.3	52.3	38.4	29.4	23.2	18.8
	LIVE LOAD/DEFLECTION	92.5	70.4	42.2	26.5	17.8	12.5	9.1
4-SPAN	NEGATIVE WIND LOAD	109.9	70.3	48.8	35.9	27.5	21.7	17.6
	LIVE LOAD/DEFLECTION	89.1	65.7	44.7	28.2	18.9	13.3	9.7

26 Gauge (Fy = 60 KSI)								
SPAN TYPE	LOAD TYPE	SPAN IN FEET						
		2.0	2.5	3.0	3.5	4.0	4.5	5.0
SINGLE	NEGATIVE WIND LOAD	120.0	76.8	53.3	39.2	30.0	23.7	19.2
	LIVE LOAD/DEFLECTION	96.1	49.2	28.5	17.9	12.0	8.4	6.2
2-SPAN	NEGATIVE WIND LOAD	123.2	78.9	54.8	40.2	30.8	24.3	19.7
	LIVE LOAD/DEFLECTION	120.0	76.8	53.3	39.2	29.0	20.3	14.8
3-SPAN	NEGATIVE WIND LOAD	154.0	98.6	68.5	50.3	38.5	30.4	24.6
	LIVE LOAD/DEFLECTION	149.2	92.9	53.8	33.9	22.7	15.9	11.6
4-SPAN	NEGATIVE WIND LOAD	143.8	92.0	63.9	47.0	36.0	28.4	23.0
	LIVE LOAD/DEFLECTION	139.7	89.6	57.1	35.9	24.1	16.9	12.3

NOTES:

- 1) Allowable loads are based on uniform span lengths and Fy = 60-ksi.
- 2) LIVE LOAD is limited by bending, shear, combined shear & bending and web crippling.
- 3) **NEGATIVE WIND LOAD does not contain a 33.333% increase and does not consider fastener pullout or pullover.**
- 4) Above loads consider a maximum deflection ratio of L/180.
- 5) The weight of the panel has not been deducted from the allowable loads.
- 6) The use of any accessories other than those provided by the manufacturer may damage panels, void all warranties and will void all engineering data.
- 7) This material is subject to change without notice. Please contact MBCI for most current data.

The Engineering data contained herein is for the expressed use of customers and design professionals. Along with this data, it is recommended that the design professional have a copy of the most current version of the *North American Specification for the Design of Cold-Formed Steel Structural Members* published by the American Iron and Steel Institute to facilitate design. This Specification contains the design criteria for cold-formed steel components. Along with the Specification, the designer should reference the most current building code applicable to the project jobsite in order to determine environmental loads. If further information or guidance regarding cold-formed design practices is desired, please contact the manufacturer.