



PANEL THICKNESS

LS-36™ INSULATED WALL PANEL

THROUGH PANEL FASTENER W/ WASHER @ 12" O.C.

SUPPORT ANGLE
1 1/2" x 2 1/2"
14 GA. GALVANIZED

1/4"
1/4"

STACK JOINT TRIM
1/4-14 x 7/8 LAPTEK W/ WASHER
[FASTENER #4A] @ 12" O.C.

1" x 1/8" TAPE SEALER [7300]

OUTSIDE CLOSURE [HW-456]

LS-36™ INSULATED WALL PANEL

NON-SKINNING BUTYL SEALANT [7100] 3/8" BEAD

12-14 x 1 PANCAKE HEAD SELF-DRILLER [FASTENER #12A] @ 5'-0" O.C. (TRIM TO ANGLE)

12-14 x 1 PANCAKE HEAD SELF-DRILLER [FASTENER #12A] @ 12" O.C. (ANGLE TO ANGLE)

12-14 x 1 SELF-DRILLER W/WASHER [FASTENER #17] @ 12" O.C. OR AS SPECIFIED

SHEETING ANGLE

COLD FORM WALL MEMBER (SHAPE & ORIENTATION MAY VARY)

NON-SKINNING BUTYL SEALANT [7100] 3/8" BEAD

THROUGH PANEL FASTENER W/ WASHER @ 12" O.C.